

E		F	
REV(版本)	DESCRIPTION(描述)	NAME(名字)	DATE(日期)

NOTE:

- MATERIAL:
 - HOUSING: PA9T, UL 94V-0
 - TERMINAL: C2680
- FINISH:
 - TERMINAL: NICKEL 50 μ MIN UNDER PLATED OVERALL, Au PLATED ON THE CONTACT AREA. OR Tin ON THE SOLDERING AREA.
- PRODUCT SPECIFICATION
 - CURRENT RATING : 5A
 - VOLTAGE RATING : 30V AC
 - DIELECTRIC WITHSTANDING VOLTAGE: 500VAC
 - INSULATION RESISTANCE: 100M Ω min.
 - CONTACT RESISTANCE: 30m Ω Max.
 - Operating Temperature: -40° ~105°

Pos.No.	P/N.	DIM.A	DIM.B	DIM.C	DIM.D
2Pin	5001-DP2045D-02MT-00	9.65	2.00	8.25	7.15
3Pin	5001-DP2045D-03MT-00	11.65	4.00	10.25	9.15
4Pin	5001-DP2045D-04MT-00	13.65	6.00	12.25	11.15
5Pin	5001-DP2045D-05MT-00	15.65	8.00	14.25	13.15
6Pin	5001-DP2045D-06MT-00	17.65	10.00	16.25	15.15
7Pin	5001-DP2045D-07MT-00	19.65	12.00	18.25	17.15
8Pin	5001-DP2045D-08MT-00	21.65	14.00	20.25	19.15
9Pin	5001-DP2045D-09MT-00	23.65	16.00	22.25	21.15
10Pin	5001-DP2045D-10MT-00	25.65	18.00	24.25	23.15
11Pin	5001-DP2045D-11MT-00	27.65	20.00	26.25	25.15
12Pin	5001-DP2045D-12MT-00	29.65	22.00	28.25	27.15
13Pin	5001-DP2045D-13MT-00	31.65	24.00	30.25	29.15
14Pin	5001-DP2045D-14MT-00	33.65	26.00	32.25	31.15
15Pin	5001-DP2045D-15MT-00	35.65	28.00	34.25	33.15

东莞市文章济美电子有限公司

品名 (TITLE) BATTERY MALE 90° 2.0PITCH BOARD TO BOARD CONNECTOR	制图 (DR)		XIAO
	校对 (CHKD)		Alex
	审核 (APPD)		
料号 (DWG. NO)	5001-DP2045D-**MT-00		
比例 (SCALE)	1:1	单位 (UNITS)	mm
页码 (SHEET)	1 OF 1	SIZE	A4
REV	A		

一般公差 (TOLERANCE)
X $\pm$.50 XX $\pm$.10
Y $\pm$.20 XXX $\pm$.05
ANGLES $\pm$ 1°

Recommended P.C.B Layout