



备注:

1. 产品规格:

- 1-1. 插入力: 35N MAX.
- 1-2. 拔出力: 10N MIN. INITIAL 8-20N AFTER
- 1-3. 额定电流: 1.0A
- 1-4. 额定电压: 30V
- 1-5. 耐久性: 10000 CYCLES MIN.
- 1-6. 耐电压: 100V AC MIN.
- 1-7. 接触阻抗: 30mΩ MAX. INITIAL; 40mΩ MAX AFTER
- 1-8. 绝缘电阻: 100MΩ MIN
- 1-9. 工作温度: -30° TO +80°

2. 材质:

- 2.1 胶芯: LCP UL94V-0
  - 2.2 端子: C2680R-H, 镍底, 镀金 1μ"
  - 2.3 外壳: SUS201/301, 表面镀雾锡/镀镍
3. 重点尺寸标识"▲"符号

## 东莞市文章济美电子有限公司

TOLERANCE: X.X ±0.30 X.XX ±0.20 X.XXX ±0.10 X. ±10° X° ±8° .X° ±5°	DRAWN BY:	DATE:	PART NAME:
	刘志强		MC5P母座5.9插板直边
 UNIT: mm [inch] SCALE: 1:1 SIZE: A4	CHECKED BY:	DATE:	PART NO. 5001-UMK059Z01-01R1-00
	李毅		MOLD NO.
	APPROVED BY:	DATE:	DRAW NO. 500100000110
	张少辉		SHEET NO. 1 OF 1