




REV	ECN. NO.	DESC.	APPD.
A	WE211008	新版发行	LWW 211013

NOTES: (UNLESS OTHERWISE SPECIFIED)

1. DIMENSION SHALL BE INTERPRETED PER ANSI Y14.5M-1994
2. INSERTION FORCE: 150g MAX. PER CONTACT.
3. WITHDRAW FORCE: 25g MIN. PER CONTACT.
4. DURABILITY: 30 CYCLES .
5. VOLTAGE RATING:50V AC
6. CURRENT RATING:1.0 AMPERE.
7. CONTACT RESISTANCE:50 m ohms MAX. FOR INITIAL.
8. DIELECTRIC WITHSTANDING VOLTAGE: 500V AC rms./MINUTE.
9. INSULATION RESISTANCE: 100 Megohms MIN..
10. HARMFUL MATERIAL SHOULD BE COMPLANT TO DOC. STANDARDS.
11. PRODUCT NUMBER MATRIX:
5001-BAP08S1-**-FR-00

包装: REEL
FORMATE: 每盘
PIN 间距: 2.54mm
0.8 Pitch
JAECONN BTB CONNECTOR SERIES



RECOMMEND PCB LAYOUT TOLERANCE ±0.05

CIRCUITS	DIM.A	DIM.B	DIM.C	DIM.D	DIM.E	DIM.F
40	15.20	21.80	20.20	20.10	18.70	17.70
60	23.20	29.80	28.20	28.10	26.70	25.70
80	31.20	37.80	36.20	36.10	34.70	33.70
100	39.20	45.80	44.20	44.10	42.70	41.70
120	47.20	53.80	52.20	52.10	50.70	49.70
140	55.20	61.80	60.20	60.10	58.70	57.70
160	63.20	69.80	68.20	68.10	66.70	65.70
180	71.20	77.80	76.20	76.10	74.70	73.70
200	79.20	85.80	84.20	84.10	82.70	81.70

NAME<INTENDED USE>:

0.8MM BTB CONN.

东莞市文萃齐美电子有限公司

PART NO.<INTENDED USE>:

5001-BAP08S1-**-FR

CUSTOMER DRAWING

APPD:

DWG NO.:

CHKD:

600-0000-0399

DR:

SCALE	SHEET	REV
N/A	1/1	A